ISSUED: 04/04/01 SUPERSEDES: NEW

Cribari Vineyards, Inc.

4180 West Alamos Avenue Fresno, CA 93722 (559) 277-9000 Port SLT.doc Page 1 of 2

RAW MATERIAL SPECIFICATION

CALIFORNIA PORT – SALTED

REVISION	11/14/12	AUTHORIZATION	J. CRIBARI
		PREPARED BY	K. ANSON
NATURE OF REVISION			
DISTRIBUTION			

I. <u>DESCRIPTION</u>

Product is a California Port, full bodied, salted desert wine..

II. SPECIFICATION LIMITS

Product shall be in compliance with all applicable Federal, State and Local Regulations.

A. Physical

<u>CHA</u>	RACTERISTIC	LIMIT
1.	Appearance	Dark Red liquid
2.	Flavor and Aroma	Fruity, slightly aromatic, with no foreign off odors or flavors.
3.	Weight per gallon	Approximately 8.3lbs

B. <u>Chemical</u>

(CHAR	RACTERISTIC	LIMIT	METHOD	ANALYSIS REF.
1	l .	Alcohol	17.0% - 19.0%	Anton Paar Alcolyzer	A.O.A.C. 17 th Ed. 980.2
2	2.	SO2 Free	40.0 ppm max	Ripper	MAM & W (p.206) 1980
3	3.	SO2 Total	200.0 ppm max	Ripper	A.O.A.C. 13 th Ed. 11.069
4	1.	Acidity	0.30to 0.80g/100ml	Titration	A.O.A.C. 13 th Ed. 11.037
5	5.	pН	3.0 - 3.9	pH Meter	A.O.A.C. 13 th Ed. 11.036
6	5.	Copper	0.020 ppm	Atomic Absorption	A.O.A.C. 13 th Ed. 9.029

ISSUED: 04/04/01 SUPERSEDES: NEW

Cribari Vineyards, Inc. RAW MATERIAL SPECIFICATION

Port SLT.doc Page 2 of 2

CALIFORNIA PORT – SALTED

C. Chemical, cont'd

<u>CHA</u>	RACTERISTIC	LIMIT	METHOD	ANALYSIS REF.
7.	Iron	0.0 - 7.0 ppm	Atomic Absorption	A.O.A.C. 13 th Ed. 11.022
8.	Salt	1.5% - 1.7%	Titration	A.O.A.C. 13 th Ed.

This product shall comply with California's Department of Health Services Sections 17010, Provisions Applicable to Wine Produced in California, and Section 17015, Wines Bearing the Appellation of Origin "California" or a Geographical Subdivision Thereof.

III. PACKAGING

- A. Food grade plastic containers approximately 57 gallons
- B. Larger containers up to tank truck available.

IV. STORAGE

Wine should be kept in full containers and protected from air. Shelf life of unopened plastic containers is 4 to 8 months, depending on storage temperature. Should be stored at 55 to 75 F and shipped at ambient temperature.